

ARTU900 ARTU950 ARTU901

REF. 2474

REF. 2478

REF. 2475

ARTU951 ARTU902 ARTU952

REF. 2479


REF. 2476

REF. 2480

ARTU903

REF. 2477

- Sturdy injection-moulded zinc alloy housing.
- Flush mounting in box Ø56 mm.
- Dimensions of coverplate: 80x80 mm.
- Fast and easy connection of the coaxial cable.
- Surface mounting using the ABT-210 (Ref. 1460).
- Versions without coverplate available.
- Connectors TV/RD: male IEC, SAT: female IEC.



ARTU-900 ARTU-950 ARTU-901 ARTU-951 ARTU-902 ARTU-952 ARTU-903

Frequency range		MHz	TV/RD: 5-862, SAT: 950-2300				
Transfer loss (±0.5 dB)	input - TV/RD	dB	4,5	11	15	19	
	input - SAT		5,5	11	15	18	
Max through loss	5-862 MHz	dB	-*	2	1,3	1,3	
	950-2300 MHz		-*	3	2,5	2,5	
Isolation	output - TV/RD	dB	-*	> 23	> 26	> 25	
	output - SAT		-*	> 16	> 17	> 19	
TV/RD - SAT isolation		dB	> 25				
DC transit through the SAT output			Yes	No		Yes	
Coverplate and fixing hooks			Yes	No	Yes	No	Yes

* ARTU900 and ARTU950 are final outlets.

