

DiSEqC SWITCHES

Multi Satellite Reception

APPLICATION

Fenger FDS DiSEqC switches are used in multi satellite installations for switching between 2 or 4 universal LNBs each pointing at different satellites.

FEATURES & BENEFITS

- Selects satellite signals through DiSEqC commands supplied from satellite receiver
- Utilizes one coaxial cable to transmit control instruction and satellite signal simultaneously
- Supports bi-directional DiSEqC full control functions
- Compatible with most types of satellite receiver
- Professional SMD technology design
- Zinc die-cast housing, nickel-plated
- Waterproof cover for outdoor installation
- All ports F-female connector, 75 Ohm
- Frequency range 950~2300 MHz
- Insertion loss ≤ 3 dB
- Return loss ≥ 8 dB
- Isolation ports ≥ 25 dB
- DC pass 12~20 V, max. 500 mA
- CE certification

ORDERING INFORMATION

516122..... FDS-21W, DiSEqC 2.0 Switch 2x1,
Waterproof Cover

516124..... FDS-41W, DiSEqC 2.0 Switch 4x1,
Waterproof Cover

Specifications subject to change without notice
All rights reserved. 20120511.FDS24W
DiSEqC is a trademark of EUTELSAT

FENGER[®]

CE

