

LEMCO®

DIGITAL TV SOLUTIONS

micro
line

MLC-301

2xDVB-S/S2/S2X + 2xFlexCAM to 4xDVB-T/C + IP



Features

- 2 x independent multi-standard inputs DVB-S/S2/S2X
- 2 x FlexCAM
- 4 x RF output DVB-T/C (software selectable)
- "Multistream" reception support
- Gbit IP streaming (up to 64 x SPTS / 4 x MPTS)
- "Pool" technology
- MER value > 42dB
- PID filtering
- Dual power supplies offering redundancy mode
- Custom NIT/SDT
- Local or remote control via webserver
- Very friendly user interface
- Wall or rack mount options
- SNMP v2
- Ultra-compact size
- 5-year warranty

www.lemco.tv



MLC-301

2xDVB-S/S2/S2X + 2xFlexCAM to 4xDVB-T/C + IP



- ◆ The MLC-301 is a very powerful, all-in-one mini headend device, able to receive up to 2 independent satellite (DVB-S/S2/S2X) signals with 2x CI interfaces and convert them either in 4 x DVB-T/C RF output channels or in IPTV streaming using UDP/RTP protocols multi-cast/unicast. Moreover, the MLC-301 supports "multistream" satellite reception too. The FlexCAM technology provides the ability to the user to connect the CAMs either at the inputs or the outputs of the device.
- ◆ It supports "pool" technology, meaning that the user is able to select any program from any of the 2 inputs and assign them to any of the 4 RF or IP outputs providing great flexibility.
- ◆ The embedded web server of the MLC-301 provides a very friendly user interface as well as the ability of remote or local control of the device via LAN.
- ◆ Its small size and its powerful features render the MLC-301 the ideal solution in case we want to distribute FTA (Free-To-Air) or scrambled TV programs coming from satellite (DVB-S/S2/S2X) sources to a CATV installation using the DVB-T/C or IPTV technology.

Technical Specifications

Input	
Type	2 x DVB-S/S2/S2X
Frequencies	950...2150 MHz DVB-S/S2/S2X
Multistream support	Yes
Connector	75Ω - F, female
Descrambling	Yes, Accepts 2 x universal CAM capable of connecting either on input or output

LNB	
Voltage	OFF / 13V / 18V
Current	Less than 400mA
22 kHz signal	On / Off
22 kHz signal - Voltage	0.65V ±0.35V
22 kHz signal - Frequency	22 KHz ±4Hz
22 kHz signal - DiSEqC	1.0 (Port A, B, C, D)

DVB-S (IN)	
Symbol rate	1 - 55 MBaud
Roll off factor	0.2, 0.25, 0.35
Code rate	1/2, 2/3, 3/4, 5/6, 7/8 (αυτόματο)
Spectral inversion	Reverse, Non-reverse (αυτόματο)

DVB-S2 (IN)	
Constellation	QPSK, 8PSK (Automatic)
Symbol rate	1 - 55 MBaud (QPSK) 1 - 45 MBaud (8PSK)
Roll off factor	0.2, 0.25, 0.35 (Automatic)
Code rate	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 (QPSK-Automatic) 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 (8PSK-Automatic)
Spectral inversion	Reverse, Non-reverse (Automatic)

DVB-S2X (IN)	
Constellation	QPSK, 8PSK (Automatic)
Symbol rate	1 - 45 MBaud (QPSK) 1 - 30 MBaud (8PSK)
Roll off factor	Από 0.05 έως 0.35 (Automatic)
Code rate	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 (QPSK-Automatic) 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 (8PSK-Automatic)

Transport Stream Processing	
Services	User selection by service names
Automatic regeneration	PAT, CAT, SDT, PMTs, EITs tables
NIT	Pass-through, custom, automatic
PCR	re-stamping
LCN support	Yes

RF Output	
Type	4 x RF out in adjacent channels
Output Frequencies	110...950 MHz (1 Hz step)
Output Level	90dBuV
Connector	75Ω - F, female
Output Attenuator	0...-20dB
MER	More than 42dB

DVB-T (OUT)	
Bandwidth	5, 6, 7, 8 MHz
Mode	2K, 8K
Constellation	QPSK, 16QAM, 64QAM
Guard interval	1/4, 1/8, 1/16, 1/32
Code rate	1/2, 2/3, 3/4, 5/6, 7/8

DVB-C (OUT)	
Bandwidth	5, 6, 7, 8 MHz
Mode	2K, 8K
Constellation	16QAM, 32QAM, 64QAM, 128QAM, 256QAM
Symbol rate	1-7.2 Ms/s

IP Streaming	
IP TS Out	Yes
Protocol	UDP / RTP (Multicast/Unicast)
Speed	1 Gbit
IGMP support	Yes, v2, v3
Type	MPTS (up to 4 TS) SPTS (up to 64TS)
Max. bitrate	480Mbps max.

Programming Interface	
Ethernet webserver	Yes, embedded webserver
Speed	10/100 Mbps
Connector	RJ45
Browser compatibility	Chrome, Firefox, Safari, Opera, Edge et al.

General	
Power supply	2 x +12VDC
Power supply consumption	1.8A max.
Operating temperature	0 °C to 40 °C
Storage temperature	-10 °C to +70 °C
Humidity	Up to 90%
Dimensions	235 x 115 x 48 mm
Weight	450 g



LEMCO
DIGITAL TV SOLUTIONS

46 Latheas str. - 13678 / Athens - Greece

Tel: +30 210 2811401, +30 210 2405237 - Fax: +30 210 2825755

Email: info@lemco.gr - www.lemco.tv

follow us: [facebook.com/Lemco](https://www.facebook.com/Lemco) twitter.com/lemcodtv [linkedin.com/company/lemco](https://www.linkedin.com/company/lemco)