

micro line

Quick start Guide

1. INTRO

4xHD to IP

Congratulations on purchasing the MLH-201. You now own a high quality, professional mini DTV headend. To get the most out of your purchase, please take the time to carefully read through this quick start guide.

2. INSTRUCTIONS

2.1 - Description

The MLH-201 is a very powerful, all-in-one mini headend device, able to receive up to 4 HDMI signals and convert them either in IPTV streaming using UDP/RTP protocols multicast/unicast.

The embedded web server of the MLH-201 provides a very friendly user interface as well as the ability of remote or local control of the device via LAN.

Its small size and its powerful features render the MLH-201 the ideal solution in case we want to distribute HDMI content eg. coming from STBs or Blu-ray to a CATV installation using the IPTV technology.



Quick start guide | MLH-201 4xHD to IP |

2.2 - Features

- ▶ 4 x HDMI inputs (up to 1080-30p)
- **■** DHDCP support
- Gbit IP streaming (up to 64 x SPTS / 4 x MPTS)
- Dual power supplies offering redundancy mode
- Local or remote control via webserver
- Very friendly user interface
- Wall or rack mount options
- SNMP v2
- DUltra-compact size
- 5-year warranty

3. INSTALLATION

The MLH-201 has a very friendly interface for programming and monitoring purposes. The user is able to gain access to the embedded webserver, by opening an Internet browser (e.g. Internet Explorer, Firefox or Chrome) that supports HTML 5.0 and type the following static IP: 192.168.1.205.

The default username and password are the following:

Username: admin Password: 12345

More information:

■ ▶ You can download full manual at www.lemco.tv

Contact Information Lemco IKE

Latheas 46 - 13678 Tel: +30 210 2811401 Athens - Greece Fax: +30 210 2825755 www.lemco.tv Email: info@lemco.gr

