

MFD 411 DiSEqC 4Sat+1Ter x1out

Art. Number 300495



### MFD series DiSEqC 2.0 bi-directional

- DiSEqC 2.0 compatible
- 2 or 4 SAT inputs
- TER in (MFD 411)
- Illuminated LED on the active output
- TRIAX easy mount ABS mast housing

## Technical Specifications

### ORDER INFORMATION

EAN Number 5702663004955

### CHARACTERISTICS

DiSEqC control DiSEqC 2.0

### FREQUENCY RANGE

Frequency range SAT | MHz 950...2250 MHz

Frequency range TER | MHz 47...694 MHz

### LOSS

Through loss | dB 5.5 (TER: 3.0) dB

### ISOLATION

Isolation input A-B | dB 30 dB

### ELECTRICAL

Number of positions 4

Switch Type DiSEqC

### OPERATIONAL

DC Passthrough Yes (max. 500mA)

DC Current consumption | mA < 40 mA

### CONNECTORS



## Technical Specifications

Number of inputs	4
Number of outputs	2

### MECHANICAL

Product Height   mm	57 mm
Product Width   mm	140 mm
Product Depth   mm	110 mm
Packaging Height   m	0.060 m
Packaging Width   m	0.140 m
Packaging Depth   m	0.120 m
Packaging Volume   m <sup>3</sup>	0.001 m <sup>3</sup>
Net Weight   kg	0.241 kg
Tara Weight   kg	0.039 kg
Total Weight   kg	0.280 kg